

What is claimed is:

1. A process for producing brochures, comprising:  
inserting a binding element into perforations along the edge of a plurality of superposed sheet-like material; and  
forming said binding element immediately before said inserting.
2. The process of claim 1, further comprising tailoring said binding element to complement said perforations.
3. The process of claims 1 further comprising forming a loop in said binding element and a crimp in said loop.
4. The process of claim 1 further comprising forming a series of crimps in said binding element.
5. The process of claim 1 further comprising forming several loops in said binding element, and forming a plurality of crimps in said binding element, loop by loop, with a single bending die.
6. The process of claims 1 wherein said binding element comprises a single element corresponding to a width of said brochure.
7. The process of claims 1 further comprising forming a plurality of loops in said binding element in a row that extends across a width of said brochure, and inserting said loops into said perforations at the same time.
8. The process of claim 1, further comprising determining at least one production parameter with an electronic control device.
9. The process of claim 8, wherein said binding element is formed from wire and said at least one production parameters is brochure thickness, wire diameter, wire length, or perforation spacing.

10. A process for producing brochures using wire binding, comprising:
- a) determining a thickness of a brochure to be produced and storing said thickness in an electronic device;
  - b) producing a binding element corresponding to said thickness by
    - feeding a wire from at least one wire supply containing a wire spool to a wire bending device via a conveyor,
    - bending said wire into a flat, multiple looped binding element,
    - cutting said binding element and conveying it to an insertion device;
  - (c) supplying sheet-like material to said insertion device, said material having perforations;
  - (d) inserting said binding element into said perforations; and,
  - (e) bending said binding element into a ring-like binding.
11. The process of claim 10, further comprising tailoring said binding element to complement said perforations.
12. The process of claims 10 further comprising forming a crimp in a loop.
13. The process of claim 10 further comprising forming a series of crimps in said binding element.
14. The process of claim 10 further comprising forming a plurality of loops in said binding element and forming a plurality of crimps in said binding element, loop by loop, with a single bending die.
15. The process of claims 10 wherein said binding element comprises a single element corresponding to a width of said brochure.
16. The process of claims 10 further comprising forming several loops in said binding element in a row that extends across a width of said brochure, and inserting said loops into said perforations at the same time.

17. The process of claim 10, further comprising determining production parameters with an electronic control device.
18. The process of claim 17, further comprising producing said binding element according to one or more production parameters in addition to thickness.
19. The process of claim 18, wherein at least one of said production parameters is wire diameter, wire length, or perforation spacing.
20. A process for producing brochures using wire binding, comprising:
  - a) determining a thickness of a brochure to be produced and storing said thickness in an electronic device;
  - b) producing a binding element corresponding to said thickness by
    - feeding a wire from at least one wire supply containing a wire spool to a wire bending device via a conveyor,
    - bending said wire into a flat, multiple looped binding element,
    - cutting said binding element and conveying it to an insertion device;
  - (c) supplying sheet-like material to said insertion device, said material having perforations;
  - (d) inserting said binding element into said perforations immediately after producing said binding element; and,
  - (e) bending said binding element into a ring-like binding.